



## PROHT

- Construcción de acero inoxidable
- Tanque construido en acero inoxidable 316L cal. 14 y el resto del equipo en inoxidable 304
- Provistos de generadores Neptune C®, sweepSONIK™ o multiSONIK™
- Ultrasónicos de alto desempeño
- Calefacción controlada por termostato
- 120 o 240 Vac, una fase
- Barrido de frecuencias ultrasónicas que mejoran la efectividad de la limpieza
- Cavitación uniforme con desgasificación rápida
- Frecuencias sencillas y múltiple



## PROHT - Series

1206 / 2406 / 3606 / 6006 / 1212 / 2412 / 3612  
1812 / 2016 / 2020 / 2424 / 3624



CLEANING TECHNOLOGIES GROUP

RANSOHOFF • BLACKSTONE-NEY ULTRASONICS • CTG ASIA

**Igor Pinto** (01) 800 841 2863  
Business Development Manager, Mexico  
info@ctgclean.com  
www.ctgclean.com

**Blackstone-NEY Ultrasonics**  
(800) 766-6606  
P.O. Box 220  
9 N. Main St.  
Jamestown, NY 14702-0220

**Ransohoff**  
(800) 248-9274  
4933 Provident Drive  
Cincinnati, OH 45246

**CTG Asia**  
(86)0512-66161698  
56 Songshan Road  
Suzhou New District  
Jiangsu Province, China PRC: 215151



# CLEANING TECHNOLOGIES GROUP

RANSOHOFF • BLACKSTONE-NEY ULTRASONICS CTG ASIA

MODELO	PROHT-1206	PROHT-2406	PROHT-3606	PROHT-6006	PROHT-1212	PROHT-2412
VOLTAJE	120V	120V	120V	120V	240V	240V
CAPACIDAD	1.88 Gal (7.1 Ltrs)	3.7 Gal (14 Ltrs)	5.6 Gal (21.2 Ltrs)	9.4 Gal (35.6 Ltrs)	5.6 Gal (21.2 Ltrs)	11.2 Gal (42.4 Ltrs)
DIMENSIONES DEL TANQUE (Pr x An x Al)	305mm x 152mm x 203mm	610mm x 152mm x 203mm	914mm x 152mm x 203mm	1524mm x 152mm x 203mm	305mm x 305mm x 279mm	610mm x 305mm x 279mm
VOLUMEN DE TRABAJO (Pr x An x Al)	12"x6"x8"	24"x6"x8"	36"x6"x8"	60"x6"x8"	12"x12"x11"	24"x12"x11"
DIMENSIONES DE LA UNIDAD (Pr x An x Al)	457mm x 305mm x 356mm	762mm x 305mm x 356mm	1067mm x 305mm x 356mm	1676mm x 305mm x 356mm	457mm x 457mm x 432mm	762mm x 457mm x 432mm
DIMENSIONES DE LA UNIDAD (Pr x An x Al)	18"x12"x14"	30"x12"x14"	42"x12"x14"	66"x12"x14"	18"x18"x17"	30"x18"x17"
POTENCIA ULTRASONICA	240 Watts	600 Watts	960 Watts	1,440 Watts	480 Watts	960 Watts
POTENCIA CALORIFICA	600 Watts	1,200 Watts	2,000 Watts	3,000 Watts	1,200 Watts	2,000 Watts

MODELO	PROHT-3612	PROHT-1812	PROHT-2016	PROHT-2020	PROHT-2424	PROHT-3624
VOLTAJE	240V	240V	240V	240V	240V	240V
CAPACIDAD	16.8 Gal (63.6 Ltrs)	11.2 Gal (42.4 Ltrs)	16.6 Gal (62.9 Ltrs)	24.2 Gal (91.6 Ltrs)	34.9 Gal (132.1 Ltrs)	52.4 Gal (198.4 Ltrs)
DIMENSIONES DEL TANQUE (Pr x An x Al)	914mm x 305mm x 279mm	457mm x 305mm x 356mm	508mm x 406mm x 356mm	508mm x 508mm x 406mm	610mm x 610mm x 406mm	914mm x 610mm x 406mm
VOLUMEN DE TRABAJO (Pr x An x Al)	36"x12"x11"	18"x12"x14"	20"x16"x14"	20"x20"x16"	24"x24"x16"	36"x24"x16"
DIMENSIONES DE LA UNIDAD (Pr x An x Al)	1067mm x 457mm x 432mm	610mm x 457mm x 508mm	660mm x 559mm x 508mm	660mm x 660mm x 559mm	762mm x 762mm x 559mm	1067mm x 762mm x 559mm
DIMENSIONES DE LA UNIDAD (Pr x An x Al)	42"x18"x17"	24"x18"x20"	26"x22"x20"	26"x26"x22"	30"x30"x22"	42"x30"x22"
POTENCIA ULTRASONICA	1,680 Watts	960 Watts	960 Watts	1,920 Watts	2,880 Watts	3,840 Watts
POTENCIA CALORIFICA	3,000 Watts	2,000 Watts	3,000 Watts	4,000 Watts	5,000 Watts	7,000 Watts